



# Technical Specifications

## ABNT NBR ISO 13006

Dry-pressed ceramic tiles with low water absorption  $E_v \leq 0,5\%$  Group Ia

## Bianco Di Lucca

Line Timeless

Tipology

**Glazed  
Porcelain Tile**

Code

**200889E**

Format

**120X120**

Thickness

**10,00**

Work Size

**119,85X119,85**

Edge

**Rectified**

Surface

**Polish**

Settling Joint

**1,5 mm**

### Physical Property

Water Absorption (%)	ISO 10545-3	0,5
Modulus of Breaking Strength (N/mm <sup>2</sup> )	ISO 10545-4	40
Breaking Load (N)	ISO 10545-4	2000
Moisture Expansion (mm/m)	ISO 10545-10	0,1
Crazing Resistance	ISO 10545-11	Resist
Frost Resistance	ISO 10545-12	Resist
Resistance to Thermal Shock	ISO 10545-9	Resist

### Test Standards

### Results

### Chemical Property

#### Resistance to Staining

Glazed Tiles	ISO 10545-14	3
--------------	--------------	---

#### Resistance to Chemicals

Resistance to low concentrations of acids and alkalis	ISO 10545-13	LB
Resistance to household chemicals and swimming pool salts	ISO 10545-13	A

### Test Standards

### Results

## Coefficient of Friction

## Test Standards

## Results

Dry Surface

ABNT NBR 16919

0,3

Wet Surface

ABNT NBR 16919

0,3

## Local of Use

CI - Commercial Light | RE - Residential | FA - Facade

# Portobello



Portobello SA - Fábrica | contato@portobello.com.br

SAC: 800 648 2002 1 BR 101 - Km 163 - Cx. Postal 15

Tijucas/SC - Brasil - 88200-000