

CLEANMAX

epoxy remover



PRODUCT INDICATION / DESCRIPTION

CleanMax Epoxy Remover is a colorless gel indicated for cleaning acrylic resin and epoxy based grout residues. It also removes stains paint and varnish stains. Indicated for ceramic, porcelain, marble and granite floors.

IMPORTANT: The compatibility of the CleanMax Epoxy Remover and the type of coating must be tested before cleaning, in order to assess the occurrence of stains. It is advisable to test in a small area (discreet, lit and easily accessible), proceeding with cleaning as indicated in the application item.

LIMITATIONS

DO NOT USE:

- Not indicated for maintenance or daily use.
- Do not apply to a heated surface.

COMPOSITION

N-methyl-pyrrolidone, solvents, thickener and alkalizer.

STORAGE AND SHELF LIFE

Store in a dry place, on pallets and in stacks of no more than 4 boxes high, in its original closed packaging. Shelf life of two (2) years from date of manufacture.

ATTENTION

- Wear gloves and safety goggles when handling the product.
- Protect metal parts (aluminum, zinc, iron, copper, etc.), gold appliqué and special paints.
- Wash objects and utensils used for measuring with plenty of running water before reuse.
- Do not mix with water, as the product comes ready for use in its original packaging.

APPLICATION

- Using a spatula, brush or paintbrush, apply CleanMax Epoxy Remover over the desired joint or area.
- The product action time will depend on the drying time and the thickness of the grout to be removed.

For thin layers, use the product according to the table below:

DRYING TIME	24 hours	48 hours	72 hours or more
ACTION TIME	10 min.	20 min.	From 30 min. to 24 hours

- Next, proceed to cleaning with water, rubbing gently with the aid of a soft cleaning fiber cloth (white).
- For thicker layers, the procedure varies according to the amount of grout to be removed. For example: for thick coats, leave it on for a maximum of 24 hours and use a soft cleaning fiber cloth to remove the grout. Then rinse with plenty of water, completely removing the applied product and leaving no residues. If necessary, repeat the operation until the grout is completely removed.
- For cleaning rough floors, use a soft nylon-bristle brush.

ESTIMATED CONSUMPTION

Approximately 50 g/m².

The reference yield value may vary according to the type and degree of soiling, type of coating used, surface porosity, etc.

PortoKoll®